

Lug & Ring Terminal Insulators

A more comprehensive line of insulators, offering a wider variety of lug and ring protection. Our lug and ring insulators can be used with starters, generators, alternators, solenoids, and other devices.



View inside the back cover for the Prop 65 Warning.



258 Series



- Protect large terminal connections from shorts
- Terminal Outside Dia: 2.3" / 58.7mm
- Post Height: 2.0" / 50.8mm
- Inside Grip Diameter: .65" / 16.6mm
- Can accept multiple cables, up to 1/0 ga each

Part #	Cable Entry Size
258N4	Round, 3/0 - 4/0
258N9	Oval, up to 4/0



216T Series



- Snap-on insulator, can be removed without cable
- Terminal Outside Dia: .64" / 16.3mm
- Post Height: .74" / 18.8mm

Part #	Cable Entry Size
216T8	.27" / 6.9mm



400 Series



- Terminal Outside Dia: .6" / 15.2mm
- Post Height: .88" / 22.4mm
- Inside Grip Dia: .44" / 11.2mm
- Terminal Length: 1.19" / 30.3mm

Part #	Cable Entry Size
400N7	.31" / 7.9mm
400N9	.44" / 11.2mm
400E4	.18" / 4.6mm



405 Series



- Terminal Outside Dia: 1.0" / 25.4mm
- Post Height: .98" / 24.8mm
- Inside Grip Diameter: .50" / 12.7mm

Part #	Cable Entry Size
405N1	.13" / 3.3 mm
405N2	.30" / 7.6mm
405N9	.50" / 12.7mm



406 Series

406N3	.16" / 4.1mm
406N9	.75" / 19mm



470 Series



- Terminal Outside Dia: .85" / 21.6mm
- Post Height: 1.06" / 26.9mm
- Inside Grip Diameter: .63" / 15.9mm
- Terminal Length: 1.81" / 46.0mm

Part #	Cable Entry Size
470N9	.63" / 15.9mm



485 Series



- Terminal Outside Dia: .52" / 12.9mm
- Post Height: .45" / 11.4mm
- Inside Grip Diameter: .25" / 6.4mm
- Cable Entry: .25" / 6.4mm

Part #	Cable Entry Size
485N9	.25" / 6.4mm



487 Series



- Terminal Outside Dia: 1.26" / 32mm
- Post Height: .98" / 24.9mm
- Inside Grip Dia: 1.0" / 25.4mm
- Available in 5 cable entries

Part #	Cable Entry Size
487N6	.5" / 12.7mm
487N7	.6" / 15.2mm
487N8	.65" / 16.5mm
487N9	.75" / 19mm
488N9	.87" / 22.1mm



488 Series