

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.

PREFERRED VENDOR:

NEXEO

MATERIAL PART NO:

1103700114

MATERIAL:

GEOLAST 701-70

VENDOR PART NO:

701-70 BLACK

SPECIFIC GRAVITY:

1.04

HARDNESS 15 SEC:

75

HARDNESS SCALE:

A

TENSILE STRENGTH, PSI:

841

ELONGATION, %:

220

TEAR STRENGTH, PPI:

114

FLAME CLASS UL:

N/A

BRITTLINESS TEMP., DEGREES F [C]:

- 14 [-25.6]

MELT TEMP., DEGREES F [C]:

215 [102]

DIELECTRIC STRENGTH, V/MIL:

N/A

		VTE Incorporated	
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF:	DATE: 21FEB17	DRN BY: RAS	WEIGHT:
		CHK'D BY: RAS	
TITLE: GEOLAST MATERIAL INFORMATION			
MATERIAL: GEOLAST		PART NO.	
COLOR: BLACK	DRG CLASS	1103700114	