

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.

PREFERRED VENDOR:

POLY ONE

MATERIAL PART NO:

1203660100

MATERIAL:

DYNAFLEX

VENDOR PART NO:

G2701-1000-02

SPECIFIC GRAVITY:

0.900

HARDNESS 10 SEC:

66

HARDNESS SCALE:

A

TENSILE STRENGTH, PSI:

1100

ELONGATION, %:

680

TEAR STRENGTH, PPI:

240

FLAME CLASS UL:

N/A

MELT TEMP., DEGREES F [C]:

190-200 [88-93]

		VTE Incorporated	
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF:	DATE: 21FEB17	DRN BY: RAS	WEIGHT:
		CHK'D BY: RAS	
TITLE: DYNAFLEX MATERIAL INFORMATION			
MATERIAL: DYNAFLEX		PART NO.	
COLOR: CLEAR	DRG CLASS	1203660100	