THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED, ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED.VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE. MATERIAL PART NO:
MATERIAL:
VENDOR PART NO:
SPECIFIC GRAVITY:
MELTING TEMP;
U.L. RATING: 0,201 [5,11] 7111210502 GLASS FILLED NYLON HYLON N2015 HL NAT 1.23 515 F (268 C) UL 94 HB 2,000 3,991 4.500 [114.30] 0.556 [50,80] [101.37] [14,12 Ø0.312 [ø7.94] Maximum Allowable Deflection DO NOT SCALE Ø0.199 [Ø5.05] 0.743 SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS: IN [mm]
TOLDRANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ±.030" [±0.8mm]
HARDWARE ITEMS: ±.010" [±0.25mm] REF: [18,87] TITLE MATERIAL: CUSTOMER DIMS. 4 brace둦 W GLASS FILLED NYLON 0.860 0.750 19.053 ADDED "ALLOWABLE DEFLECTION" NOTE REVISED MATERIAL INFORMATION DRG CLASS DATE [21,84] 04-28-04 MEGA STYLE FUSE HOLDER REVISIONS VTE INCOMPONATED 5437 Robinson Road, P.D. Box 790 Pellston, Michigan 49769 FAX: 231-539-0914 Telephone: 1-800-527-9256, 231-539-8000 ..242 [31.54] CHK'D BY: DRN BY: 336N9N02 뫄 BRY BASE 1-19-23 7-17-18 DATE .075 LBS **MEIGHT**: [33.8 RA A S RAS IJ IJ ഉ