


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

| LTR. | REVISIONS | DATE | INT. |
|------|---|-----------|------|
| A | ADDED RESET CUTOUT, RADIUS CORNER SUPPORTS | 08-APR-02 | JC |
| B | UPDATED DIMENSION FROM 1.496 [38.00] AND ADDED "REFERENCE ONLY" | 15-MAY-19 | RAS |
| C | REVISED DIMENSION FROM 0.708 [17.99] | 15-MAY-19 | RAS |

TYP. WALL THICKNESS = 1.5



SECTION A-A

SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS: in [mm]
TOLERANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ±.030" [±0.8mm]
ALL ANGLES ARE ± 1 DEGREE

| | |
|------------------------------|-----------------------|
| MATERIAL PART NO: | 1101700102 |
| MATERIAL: | PVC |
| VENDOR PART NO: | 7843-70-RED 6288 |
| SHORE DUROMETER: | "A" 10 SEC, 70 |
| SPECIFIC GRAVITY: | 1.34 |
| ULT. ELONGATION %: | 350 |
| MELTING TEMP: | 320-340 F [160-171 C] |
| BRITTLE TEMP: | -22 F [-30 C] |
| TENSILE STRENGTH PSI: | 1550 PSI |
| DIELECTRIC STRENGTH, V./mil: | 553 |
| U.L. RATING: | V0 |

| | | | |
|---|------------------|---|--------------|
|  | | VTE Incorporated 5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914 | |
| | | REF: QA DIMS | DATE: 4-1-98 |
| TITLE: SHORT STOP CIRCUIT BREAKER COVER | | | |
| MATERIAL: PVC | | PART NO. 464N0V02 | |
| COLOR: RED | DRG CLASS: REV C | | |