

Amperage ratings are for reference only. Current capacity is determined by the cables used, not the junction post. Current ratings are related to expected cable capacities.

Current Rating: 15 Amp @ 12VDC

MAXIMUM VOLTAGE: 48 VDC

MATERIAL PART NO: 1111210514UL MATERIAL: **GLASS FILLED NYLON VENDOR PART NO:** HYLON N2015 HL BK

MAX 3/8" FASTENER TORQUE: 144 IN./LBS. [16.2 Nm]

## Assembly Weight:

0.10 Lbs. [46.2 g]

ALL DIMENSIONS GIVEN AS : INCH [METRIC] TOLERANCES UNLESS OTHERWISE SPECIFIED MOLDED PRODUCTS: ±.030" / ±0.8mm HARDWARE PRODUCTS: ±.010" / ±0.25mm

PRINTED COPIES ARE NOT CONTROLLED

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED PROHIBITED.



## VTE INCORPORATED

5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 USA

Telephone: 1-800-527-9256, 231-539-8000 Fax: 231-539-0914, EFax: 231-344-5914

TITLE:

SIZE DO NOT SCALE DRAWING

**REV** 

DRAWN BY:	RAS	11-02-23	
CHECKED BY:	PJK	11-02-23	DWG. NO.

NAME

DATE

3/8" Low Profile Power Post

77337CN14