



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED.

VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

USE GREENLEE
PUNCH ASSEMBLY
#60098 FOR PANEL
CUTOUT



ASSEMBLY #7B3732N09



TOLERANCE UNLESS OTHERWISE SPECIFIED:
 MOLDED PRODUCTS ONLY: $\pm 0.30''/\pm 0.8\text{mm}$
 HARDWARE ITEMS: $\pm 0.010''/\pm 0.25\text{mm}$
 RADIAL DIAMETERS TO BE MEASURED OVER MANDRELS,
 RING GAGES OR PIN GAGES OF SUITABLE SIZE

INCLUDES P-16808110001 BLUE DOT MULTI LABEL, 1 PER CONTAINER
 MAXIMUM AMPERAGE: 300 AMPS @ 12VDC

(D)(F) MAXIMUM RECOMMENDED FASTENER TORQUE:
 S.S. JAM NUT- 160 IN./LBS.
 BRASS JAM NUT- 72 IN./LBS.

BASE MATERIAL:
 BASE MATERIAL U.L. RATING:
 VTE MATERIAL P/N:

GLASS-REINFORCED NYLON
 94 HB
 7111210509

ITEMS SHOWN FOR ILLUSTRATIVE
 PURPOSE, NOT INCLUDED:
 1/0 GA. TERMINAL LUGS (2 PLACES)

DO NOT SCALE

LTR.	REVISIONS	DATE	INT.
A	3838-000 WAS 3838, 3844-003 ADDED 2 PLCS.	02MAR07	BRH
B	ADDED CALLOUT FOR SPACER AND INSTRUCTION SHEET	01MAY07	BRH
C	3739-001 WAS 3739	08MAR11	BRH
D	MAX. TORQUE SPECS UPDATED	16OCT14	BRH
E	3844-012 WAS 3844-003	11-04-16	JMM
F	REVISED TORQUE SPEC FROM 180 IN./LBS	8-25-17	RAS

		VTE Incorporated 5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF:	DATE: 02JAN03	DRN BY: BRH CHK'D BY: BRH	WEIGHT:
TITLE: POWER BUSHING 3/8" STUD 3/8" MAX PANEL			SCALE:
MATERIAL:		PART NO. 7B3732N09	
COLOR: BLUE	DRG CLASS REV F		