


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
△	REDRAWN AND UPDATED	9-14-17	RAS



SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS: in [mm]
TOLERANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ± 0.030 [± 0.8 mm]

MATERIAL PART NO: 7203640102
MATERIAL: SANTOPRENE 201-64
VENDOR PART NO: TPE AES 201-64 NAT SANTOPRENE
SHORE DUROMETER: "A" 15 SEC. 69
SPECIFIC GRAVITY: .97
ULT. ELONGATION %: 450
MELTING TEMP: 380-450 F [193-232 C]
BRITTLE TEMP: -76 F [-60 C]
TENSILE STRENGTH PSI: 1020
DIELECTRIC STRENGTH, V./mil: 750
U.L. RATING: HB

		VTE Incorporated	
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF:	DATE:	DRN BY:	WEIGHT:
CUSTOMER DIMS	9-14-17	RAS	.028 LBS. / 12.7 G.
TITLE:		CAP FOR 955N9	
MATERIAL: SANTOPRENE		PART NO.	
COLOR: RED	DRG CLASS REV A	954N0T02	