


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
	MATERIAL CHANGED FROM PVC 95 TO GFN	06-29-16	MDL



ALL DIMENSIONS GIVEN AS: in [mm]
 MOLDED COMPONENTS: $\pm 0.030^{\circ}$ [$\pm 0.8\text{mm}$]
 HARDWARE ITEMS: $\pm 0.010^{\circ}$ [0.25mm]

VTE PART NO:
 MATERIAL:
 VENDOR PART NO:
 SPECIFIC GRAVITY:
 MELTING TEMP:
 U.L. RATING:

7111210502
 GLASS FILLED NYLON
 DURETHANE BKV 15 H 3.0 000000
 1.23
 415 F [213 C]
 UL 94 HB

		VTE Incorporated 5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914		
		REF:	DATE:	DRN BY: BRH
INSPECTION DIMS		26OCT05	CHK'D BY: BRH	.004 lbs [1.6g]
TITLE: CAVITY PLUG				
MATERIAL: GLASS FILLED NYLON			PART NO.	
COLOR: RED		DRG CLASS	329N0N02	

DO NOT SCALE