


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
△	REVISED MATERIAL INFORMATION	7-17-18	RAS



ASSEMBLY PART NUMBER	PANEL THICKNESS IN INCHES	PANEL THICKNESS IN MM	SPACER REQUIRED YES / NO	SPACER PART NUMBER
7B5050*****	0-1/16"	0-1.6MM	NO	
7B5050*****	1/16"-1/8"	1.6MM - 3.2MM	YES	330N5***
7B5051*****	1/8"-3/16"	3.2MM - 4.8MM	NO	
7B5051*****	3/16"-1/4"	4.8MM - 6.4	YES	330N5***
7B5052*****	1/4"-5/16"	6.4MM - 8MM	NO	
7B5052*****	5/16"-3/8"	8MM - 9.6MM	YES	330N5***

SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS: in [mm]
TOLERANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ±.030" [±0.8mm]
HARDWARE ITEMS: ±.010" [±0.25mm]

MATERIAL PART NO:
MATERIAL:
VENDOR PART NO:
SPECIFIC GRAVITY:
MELTING TEMP:
U.L. RATING:

7111210502
GLASS FILLED NYLON
NYLON N2015 HL NAT
1.23
515 F [268 C]
UL 94 HB

DO NOT SCALE

		VTE Incorporated		
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914		
REF:	DATE:	DRN BY:	BRH	WEIGHT:
QA DIMS	06-16-04	CHK'D BY:	BRH	.003 LBS [1.43 g]
TITLE: SPACER FOR 1/2" POWER STUD				
MATERIAL: GLASS FILLED NYLON			PART NO.	
COLOR: RED			330N5N02	
DRG CLASS			REV A	