



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
△	UPDATED .080 [2.0] TO .090 [2.3]	3-8-17	RAS



SECTION A-A
TYP. WALL THICKNESS = .090" [2.3]
TYP. RADIUS = .090" [2.3]

ALL DIMENSIONS GIVEN AS: in [mm]
MOLDED PARTS: ±.030" [±0.8mm]

VTE PART NO: 1101650109
MATERIAL: PVC
VENDOR PART NO: 9067-70-BLUE 1812
SHORE DUREMETER: "A" 10 SEC. 70
SPECIFIC GRAVITY: 1.36
ULT. ELONGATION %: 310
MELTING TEMP: 320-340 F [160-171 C]
TENSILE STRENGTH PSI: 1100
U.L. RATING: HB

		VTE Incorporated	
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF: QA DIMS	DATE: 03-27-98	DRN BY: JC	WEIGHT: .035 LBS [16.0 g]
		CHK'D BY: JC	
TITLE: BATTERY CABLE BOOT			
MATERIAL: PVC		PART NO. 415N8V09	
COLOR: BLUE	DRG CLASS REV A		

DO NOT SCALE