


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.



ALL DIMENSIONS GIVEN AS: in [mm]
MOLDED PARTS: ±.030" [±0.8mm]
HARDWARE ITEMS: ±.010" [±0.25mm]

VTE PART NO: 1101950105
MATERIAL: PVC
VENDOR PART NO: 9812-95-YELLOW
SHORE DUROMETER: "A" 10 SEC. 95
SPECIFIC GRAVITY: 1.49
ULT. ELONGATION %: 200
MELTING TEMP: 345-365 F [174-185 C]
TENSILE STRENGTH PSI: 2100
DIELECTRIC STRENGTH, V./mil: 438
U.L. RATING: V2

DO NOT SCALE

		VTE Incorporated	
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF: QA DIMS	DATE: 03-30-98	DRN BY: JC	WEIGHT: .050 LBS [22.3 g]
		CHK'D BY: JC	
TITLE: INSULATED TERMINAL COVER			
MATERIAL: PVC		PART NO. 417N9 V05	
COLOR: YELLOW	DRG CLASS		