


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
	UPDATED DIMENSIONS TO (REFERENCE DIMENSION)	13FEB17	RAS
	ADDED ANGULAR TOLERANCE	10MAR17	RAS



0.561 [14.24]
0.308 [7.83]

105°

1.000 R [25.4]

0.031 R [0.78]

0.049 [1.25]

SECTION A-A

0.379 [9.63]

1.030 [26.16]

2.330 [59.18]
(REFERENCE DIMENSION)




1.259 [31.97]

0.130 [3.30]



ALL DIMENSIONS GIVEN AS: in [mm]
MOLDED PARTS: $\pm 0.030"$ [$\pm 0.8\text{mm}$]
HARDWARE ITEMS: $\pm 0.010"$ [$\pm 0.25\text{mm}$]
ANGULAR DIMENSIONS: $\pm 5^\circ$



VTE PART NO:	1101650114
MATERIAL:	PVC
VENDOR PART NO:	9812-65-BLACK
SHORE DUROMETER:	"A" 10 SEC. 65
SPECIFIC GRAVITY:	1.34
ULT. ELONGATION %:	400
MELTING TEMP:	315-335 F [157-168 C]
BRITTLE TEMP:	-54 F [-48 C]
Tensile Strength PSI:	1550 PSI
Dielectric Strength, v./mil	453
U.L. Rating:	V2

DO NOT SCALE

		VTE Incorporated	
		5437 Robinson Road, P.O. Box 790 Pellston, Michigan 49769 Telephone: 1-800-527-9256, 231-539-8000 FAX: 231-539-0914	
REF:	DATE:	DRN BY: RAS	WEIGHT:
QA DIMS	12-07-16	CHK'D BY: RAS	.023 LBS [10.53 g]
TITLE: BOOT - HORN SWITCH			
MATERIAL: PVC		PART NO. 530N3V14	
COLOR: BLACK	DRG CLASS REV B		