



CURRENT CARRYING CAPACITY:
 DUTY CYCLE:
 CURRENT CAPACITY:
 TEMPORARY MAX (12 MINUTES)

80%
 5.2 Kw (440 AMP @ 12VDC)
 6.6 Kw (550 AMP @ 12VDC)

MAXIMUM FASTENER TORQUES:
 SEALING NUT: 10 FT./LBS.(120 IN./LBS.)

BASE MATERIAL U.L. RATING: 94 HB
 BASE MATERIAL: GLASS-REINFORCED NYLON

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	360N8N02	GFN BUSHING	1
2	3755-M03	10MM X 1.5 THREADED ROD	1
3	3864-000	COPPER CORE	1
4	3648-004	NICKEL PLATED COPPER CONTACT WASHER	2

TOLERANCES UNLESS OTHERWISE SPECIFIED :
 MOLDED PRODUCTS ONLY : $\pm .030'' / \pm 0.8\text{mm}$
 HARDWARE ITEMS : $\pm .010'' / \pm 0.25\text{mm}$
 RADIAL DIAMETERS TO BE MEASURED OVER
 MANDRELS, RING GAGES OR PIN
 GAGES OF SUITABLE SIZE



VTE INCORPORATED
 5437 Robinson Road, P.O. Box 790
 Pellston, Michigan 49769 USA
 Telephone : 1-800-527-9256, 231-539-8000
 Fax : 231-539-0914, Efax : 231-344-5914

PRINTED COPIES ARE NOT CONTROLLED
 PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 VTE INCORPORATED. ANY REPRODUCTION
 IN PART OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF VTE INCORPORATED PROHIBITED.

REV	NAME	DATE
	DRAWN BY: RAS	6/6/2016
SIZE A	CHECKED BY:	
DO NOT SCALE DRAWING		

TITLE: POWER BUSHING SUB ASSEMBLY
DWG. NO. 7376XC202