




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
	REDRAWN AND UPDATED FROM 9/20/99	5-20-22	RAS



SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS IN [mm]
TOLERANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ±0.30" [±0.8mm]
ALL ANGLES ARE ± 1 DEGREE

MATERIAL PART NO: 1101950114
MATERIAL: PVC
VENDOR PART NO: 9812-95-BLACK
SHORE DUREMETER: 4A 10 SEC. 95
SPECIFIC GRAVITY: 1.5
ULT. ELONGATION %: 200
MELTING TEMP: 345-365 F [174-185 C]
TENSILE STRENGTH PSI: 2100
DIELECTRIC STRENGTH, V./mil: 384
UL. RATING: V2



VTE Incorporated
5437 Robinson Road, P.O. Box 790
Pellston, Michigan 49769
Telephone: 1-800-527-9256, 231-539-8000
FAX: 231-539-0914

REF.	DATE:	5-20-22	DRN BY:	RAS	WEIGHT:	0.047 lbs [21.5 g]
TITLE:	OFFSET TERMINAL INSULATOR					
MATERIAL:	PVC	PART NO. 453L9V14				
COLOR: BLACK	DRG CLASS	REV A				