





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

LTR.	REVISIONS	DATE	INT.
	REDRAWN AND UPDATED FROM 9/20/99	5-20-22	RAS



MATERIAL PART NO: 1101900102
MATERIAL: PVC
VENDOR PART NO: 9812-95-RED 683
SHORE DUREMETER: "A" 10 SEC. 95
SPECIFIC GRAVITY: 1.49
ULT. ELONGATION %: 200
MELTING TEMP: 345-365 F [174-185 C]
TENSILE STRENGTH PSI: 2100
DIELECTRIC STRENGTH, V./mil: 438
UL. RATING: V2

SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS: in [mm]
TOLERANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ±.030" [±0.8mm]
ALL ANGLES ARE ± 1 DEGREE



VTE Incorporated
5437 Robinson Road, P.O. Box 790
Pellston, Michigan 49769
Telephone: 1-800-527-9256, 231-539-8000
FAX: 231-539-0914

REF:	DATE:	5-20-22	DRN BY:	RAS	WEIGHT:	0.047 lbs [21.5 g]
TITLE: OFFSET TERMINAL INSULATOR						
MATERIAL:		PVC		PART NO: 454R9V02		
COLOR:	RED	DRG	CLASS	REV A		