



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

1.125 [28.58]
USE GREENLEE PUNCH
ASSEMBLY #60098
FOR PANEL CUTOUT
Ø1.375 [34.93]



LT#	REVISIONS	DATE	INT.
1	3.07 WAS 3.25"	5-11-10	BRH
2	REDUCED FROM 550 AMP	11-17-15	RAS
3	ADDED TORQUE TAG	12-29-15	RAS
4	INCREASED FROM 350 AMP	1-01-16	RAS
5	MOVED TORQUE TAG TO OPPOSITE POST	1-27-16	RAS
6	3.09 WAS 3.07, UPDATED MATERIAL P/N	6-22-17	JMM
7	REDRAWN (ORIGINAL DRAWING 5-28-09)	11-17-17	RAS
8	UPDATED TORQUE VALUES FROM 180 IN-LBS [20.34 Nm]	2-03-18	RAS
9	ADDED IP65 STATEMENT	10-17-18	RAS
10	REMOVED TORQUE TAG	03-06-26	RAS



3.090 [78.48]
REFERENCE
ONLY

⊕ MAXIMUM FASTENER TORQUES:
JAM NUTS: 212 IN-LBS [24.0 Nm]
SEALING NUT: 120 IN-LBS [13.5 Nm]

< ASSEMBLY DESIGNED TO MEET
IP65 REQUIREMENTS >

CURRENT CARRYING CAPACITY:
80%
DUTY CYCLE:
5.2 Kw (440 AMP @ 12VDC)
CURRENT CAPACITY:
6.6 Kw (550 AMP @ 12VDC)
TEMPORARY MAX (12 MINUTES)
MATERIAL PART NO:
1111210514UL
VENDOR PART NO:
GLASS FILLED NYLON
SPECIFIC GRAVITY:
HYLON N2015 HL BK
MELTING TEMP:
1123
UL RATING:
515 F [268 C]
UL 94 HB

SCALE FACTOR : NONE
ALL DIMENSIONS GIVEN AS: In [mm]
TOLERANCES UNLESS OTHERWISE SPECIFIED :
MOLDED PARTS: ±.030" [±0.8mm]
HARDWARE ITEMS: ±.010" [±0.25mm]



VTE Incorporated
5437 Robinson Road, P.O. Box 790
Pellston, Michigan 49769
Telephone: 1-800-527-9256, 231-539-8000
FAX: 231-539-0914

REF:	DATE:	DRN BY:	RAS	WEIGHT:
CUSTOMER DIMS	11-17-17	CHK'D BY:	PJK	
TITLE:	WEATHER PROOF 3/8" POWER BUSHING, COPPER CORE			
MATERIAL:	GLASS FILLED NYLON	PART NO.	CCB376N0N02W	
COLOR:	RED	DRG CLASS	REV J	